



MYDECT.RU

**File Name:** bosch integral te 11 manual.pdf

**Size:** 4748 KB

**Type:** PDF, ePub, eBook

**Category:** Book

**Uploaded:** 22 May 2019, 18:38 PM

**Rating:** 4.6/5 from 579 votes.

**Status:** AVAILABLE

Last checked: 3 Minutes ago!

**In order to read or download bosch integral te 11 manual ebook, you need to create a FREE account.**

[\*\*Download Now!\*\*](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

### Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with bosch integral te 11 manual . To get started finding bosch integral te 11 manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



## Book Descriptions:

# bosch integral te 11 manual

Economy Telephone Integral TE 13 Connected to ISDN Telecommunications Systems Integral Operating Instructions. The alphabetic labelling allows you to dial so called vanity numbers. PQRS WXYZ Star and Hash keys for special functions. Function keys Speed dial key for dialing the numbers stored in the telephone system. You can then start the procedure over. Basic functions of your telephone Making calls internal How you do this depends on the tele calls phone system you have. This is the only way to store your en ming tries permanently. Integral 33 After you have finished your input and pressed the Redial key, you can continue in the respective program, e.g. What you should definitely read D Basic operating principles starting on p. 14. You should read this section to learn about the special features of your new tele phone, even if you are already familiar with deluxe phones. Special features of your telephone How to use this manual Basic operating rules Putting your telephone into operation Making a standard call Making calls. AEI interface Display Programmable to connect The displays assist you function keys or accessories. This section gives you a brief overview of the keys on your phone and their respective functions. The use of the individual keys is explained in detail under the corresponding function on the following pages. This telephone also offers a variety of functions that make phoning even easier. This chapter contains a brief overview of some of these special features. The display assists you The display provides you with important information, e.g. Using the phone in a partner group Your BOSCH TELECOM service representative can connect your phone to other phones within your system to form a partner group. A number of functions are particularly easy to use within this partner group. You can then, for example, receive a signal in the neighbouring room when your telephone rings. <http://tunisie.mawarids.org/mpfiles/commodore-workshop-manual-free-download.xml>

- **bosch integral te 11 manual, bosch integral te 11 manual pdf, bosch integral te 11 manual download, bosch integral te 11 manual online, bosch integral te 11 manual free.**

The second alarm is connected to the telephone's AEI interface via a switch contact. Please contact BOSCH Telecom as required. This section contains a brief description of each of these symbols. The screens used in the manual contain only the texts or symbols that are significant for the respective function. The chapter "If in doubt, look it up". Other functions may also be disabled. Consult your BOSCH TELECOM service representative if you wish to use these functions. The display assists you The figure to the left is an example of the display when the phone is in the idle mode. 1234 MILL 11.11.94 1650 You can program your phone to display FULL JONE DAVI HARR JOHN. Softkeys The functions of the top two rows of function keys change according to current operation. You do not need to remember any key symbols or combinations for menu selection. You can cancel an operation at any time if you change your mind or inadvertently activate the wrong function. Lift the handset when the caller answers. This procedure is useful, if, for example, the called party is busy and you need to redial the number several times. Setting up a call To set up a call you have to perform the two steps described below. You have three options. Lift the handset. The specified call number is dialed. If the other subscriber answers, you can make the call as usual. Press the "Monitor". You can, for example, enter text for a telephone book entry. Entering text Example telephone book If you want to store a new entry in the telephone book, use the display keys to enter Name the individual letters. Select language for display and Minimail The message shown to the left appears on the idle display. Internal Dial the desired number directly. The call number and the name of the calling party if applicable are displayed on 123321 the screen if the call is internal or set up via ISDN. Inform the

other party that someone else is listening. In addition, you and your partner hear two short beeps. <http://swadeministries.com/pastor-sammy/upload/imagecontent/commodore-vy-service-manual.xml>

Enter the first letter of the desired name. e.g. Press the "Enter" key to confirm your Enter selection. Messages and diverted calls are listed separately even if they proceed from the same subscriber. Moreover, you can directly store a call number of the call list in the telephone book. Dialing a number from the call list The message "List". The call number is now stored in the telephone book. If the called party is busy You call an internal subscriber and the line is busy. Press the "Callback". Press the "Enter" key. To use this function, enter the project code or private code before dialing an external call number. This function must be set up by the Bosch Service in the telephone system. You can also answer calls by pressing the "Microphone" key and leaving the handset onhook. Moreover, you can answer calls for other parties call pickup. You can request these info messages by calling. Call forwarding all calls to the voicemail Select the menu item "Call forwarding". There is a 11.11.94 1111 message for you in the voicemail. Enter Select the desired message type from the list. You can retrieve and, if required, immediately dial specific call numbers. Call numbers from the talk list can easily be reallocated to your telephone book. The call number is then stored in the telephone book. Deactivating the talk list If you do not wish to use the talk list, you can have it deactivated by your Bosch Service. Here, callers can leave up to 10 short minimails. The display will show you whenever you have received a new minimail. View mailbox The envelope symbol appears in the idle display indicating that you have received a 14.05.96 1111 minimail message. Listening to your partner over the loudspeaker You are making a call. Press the "Monitor" key to activate the loudspeaker. You and your call partner will hear two short tones to signal that the loudspeaker has been activated. During the call, you can adjust the loudspeaker volume and the handsfree sensitivity.

Important notes on handsfree mode Do not install the telephone in bare, reverberating rooms or in rooms with loud background noises. Press the "Handsfree mode" key. You and your call partner hear two short tones, which indicate that you have activated "Handsfree mode". Note Always tell your call partner that you have activated handsfree mode! These settings are only retained for the duration of the call. Changing settings during a call You are on the phone. Please contact your Bosch Service if you have any questions. Forwarding a second caller You receive a second call while you are on the phone. You can switch back and forth among these parties as desired. Connections to a maximum of four parties can be established simultaneously. Initiating a consultation You are on the phone. Press the "Refer back". One conference participant can be placed on hold so that you can speak with the other subscriber alone. Speaking simultaneously with two call partners conference You are on the phone. A conference can be conducted with external as well as internal subscribers. Ending a conference You are holding a conference with two call partners. A number of functions are particularly easy to use within this partner group. You can set partner beep individually for each partner. Select the "Partners". If you do not need any information on a particular partner, you can deactivate the partner display for that partner. You can choose any of these group extensions to create your own partner group. You can also restrict the status display of your phone on the phones of your partners. In addition, you can tag entries, e.g. for data connections or the VIP function. You can store call numbers contained in the main telephone book in your local telephone book. Entering new call numbers Call up the telephone book. You store a number in the redial memory on a destination key. The previously stored destination is overwritten and the new number is stored in the telephone book.

<http://www.drupalitalia.org/node/70916>

This can be accomplished in two ways. Storing call numbers on destination keys Note This option cannot be selected if "Direct dialDest.". The corresponding menu items are tagged with a small box. Accept entry To store an entry from the main telephone book in your private telephone book. Data

destination If you enter "Yes", the number can be used to set up data connections. Delete The selected entry is deleted from the phone book. Press the corresponding destination key. VIP number The call number is stored as a VIP number. If you have set the menu item "Get VIP functions". You can activate a second call diversion destination to divert calls only when your line is busy. You can set up two diversions for partners to divert the calls for a partner to your phone. This function is activated and deactivated by means of codes. Please ask your BOSCH TELECOM service representative for the codes valid for your system. Double Call is set, activated and deactivated by means of particular codes. Setting Double Call destination Lift the handset. Press the "Star". These functions can be carried out by simply pressing the corresponding key. In this way you can, for example, activate and deactivate a fixed call diversion by means of a single keystroke. Postdialing Dtmf That way you can transfer information, for example in home banking ex. In the display all basic settings which you can change are shown. Connecting handsfree equipment Plug the connecting cable of the handsfree equipment into the AEI interface on the underside of your telephone. If your call partner informs you of a less than optimal transmission quality, you can use the balancing at any time manually. This will improve handsfree mode. Connecting the auxiliary loudspeaker Plug connection AEI interface to Pull the connector from the telephone's the underside of the AEI interface. Press "Enter" key in order to confirm the Enter new setting. In doing so, the new settings are stored.

<http://gerryikputuandpartners.com/images/canon-p100-dh-user-manual.pdf>

Note If your call partner informs you of a less than optimal transmission quality, you can. The charge display for the corresponding call is deleted. Note If you wish to delete the charge total for all calls, you must have the function enabled by your BOSCH TELECOM service representative. The charges per unit are transmitted by your system and cannot be changed on your telephone. You can deactivate the charge display on your telephone. Switching the charge display to units The default setting for the charge display is amount. Your telephone retains these settings for all calls. You can separately determine the language for the Minimap texts. The available languages are English, German and French. You can enter up to ten appointments, each of which can be activated and deactivated individually. Moreover, you can easily define whether you wish to be reminded only once or every day. This tone stops after a few seconds. Cancel signal tone Press the "Release" key. This message appears on the idle display. Appointment expired. Calling parties then hear a busy signal. If you are a member of a hunt group, you can temporarily withdraw from the group if you do not want to receive calls. You can then use this telephone like your own connection. This function is protected with a PIN. In order to avoid abuse and accidental listening possibilities from other subscribers, the setup of VIP functions is protected with a PIN number. Display and process the desired entry. 1234 BERT 2345 HARR Set "VIP number" to "Yes". This text is only displayed if the called extension is busy, i.e. it is either connected to two other parties, or it is connected to one party and has deactivated second calls. Simply call the corresponding subscriber. Announcement from the executive set Prepare executive set Select the "Further functions". This is useful for example if you are often not right beside your telephone or if you have no hand free.

<http://antenasmunarriz.com/images/canon-p170-dh-manual-download.pdf>

On receiving a call the handsfree function is switched on automatically. You can answer immediately. Normal call VIP call rings with VIP ringing tone. Announcement You can make an announcement. When your phone is in idle mode this key serves to open the menu "Adjust acoustics and contrast". This function must be enabled by your BOSCH TELECOM service representative. p. 133 Lock You can protect your telephone from unauthorized users. You can also de. Any waiting calls are rejected. Set TA To change the basic settings of your terminal adapter adapting them to your requirements. Messages which can be seen in standby display are also included here. You can call up the respective menu items directly from the standby display. Symbols on the display

Someone is calling you. You can now complete a connection for this partner or the partner can dial an external number himself. You can now dial or a connection can be completed for you using the partner telephone. Someone tried to reach you while you were away or on the phone. Test loop active The test loop of the terminal adapter is active. In this case the settings for some functions are changed. Depending on the default setting, certain functions like handsfree are blocked. If the display has not been switched off corresponding messages will be displayed. This overview contains an alphabetic list of the most important menu items. Accept call If you want to answer an additional call. Your telephone must be designed with the comfort handsfree equipment for this. If necessary, consult your BOSCH TELECOM Service. Baud rate AT Here you can define the baud rate of your telephone for data transmission. Call sum The charges incurred for all calls are displayed in the form of an amount or charge units. Call with data You must set this menu item to "ON". Enter the current code PIN to unlock the telephone. Data bits AT This option permits you to define the character format for the control of your telephone.

Dial Configuring the terminal adapter Various settings facilitate the set up of incoming and outgoing or just incoming calls. Manual Asynchronous only. To support simple terminals. You can enter the call number using the terminal keyboard. This function must be enabled by your BOSCH TELECOM service representative. Div. from Call diversion from Diverts calls from one of your partners to you. If required please contact your BOSCH TELECOM Service. A lower level results in a reduction of the echo. If required please contact your BOSCH TELECOM Service. You can also determine which functions are to remain available after the lock has been activated lock levels must be enabled by your BOSCH TELECOM service representative. Login If this function is cleared in your system, you can log into every telephone in your system with your direct dialing number and a personal PIN number. Standard Only one menu item at a time is displayed. This operating mode is active when you put your telephone into operation. This function must be enabled by your BOSCH TELECOM service representative. Note Assignment Call number is entered as a note during a call. Notes can be listed separately in the telephone book. Part of group You can switch your phone in and out of a hunt group. This function must be enabled by your BOSCH TELECOM service representative. Partner Set the partner functions and partner display as you wish. This function must be enabled by your BOSCH TELECOM service representative. Restr. signaling No signaling of call modes of your phone on the phones of your partners. You can activate the no knocking function during a call. Sound VIP Change the sound pattern of VIP ringing. Start METB search You can use this menu item to search through the telephone book of your system for an entry that you cannot find in your telephone book. The telephone cannot be used during test ing. This function must be enabled by your BOSCH TELECOM service representative. Test no.

[www.optionassurance.ca/wp-content/plugins/formcraft/file-upload/server/content/files/1626c22f564a76---casio-aw81d-2av-manual.pdf](http://www.optionassurance.ca/wp-content/plugins/formcraft/file-upload/server/content/files/1626c22f564a76---casio-aw81d-2av-manual.pdf)

Test number on Checks whether the number of a calling party is stored in your telephone book as a data number. This function must be enabled by your BOSCH TELECOM service representative. VIP number You store the call number as a VIP number, i.e. the subscriber with this number is authorized to activate team functions on your phone. You and your partner hear a short special information tone. A function is not performed Your BOSCH TELECOM service representative may need to enable this function. Functions that have not been enabled are tagged with . Telephone prematurely cancels programming You may not have pressed a key during the last 60 seconds. You must specify your code before locking the phone for the first time. You may enter it yourself and change it at any time. Please consult your BOSCH TELECOM service representative if required. Setting the lock levels Select the desired menu item. You can also adapt the phone to the ambient conditions in the room also possible during a call p. 37. The speaker cannot hear Speak in turns and let each other finish speaking. If the other party tells you that the transmission quality is not

optimum, you can change the settings manually at any time. You can also make calls simultaneously depending on the connection to your telephone system. Various baud rates can be used if the data flow is actively monitored. Please refer to the respective user manual for information on the configuration of your data terminal. A malfunction is indicated on the display accordingly. Contact your BOSCH TELECOM service representative if this is the case. You must log in using your call number and code. BOSCH TELECOM cannot be held responsible for this type of damage. We therefore recommend that you place your phone on a nonslip base, particularly if the JSFiddle or its authors are not responsible or liable for any loss or damage of any kind during the usage of provided code. With Bosch's instruction manuals.

Simply enter the ENR model type number from your appliance and we'll take you to the available publications. Just use the type plate finder to get assistance. Just click on the link below to get assistance. By using our site, you agree to our use of cookies. Visit our Privacy Policy to learn more. Complete documentation is available for your Bosch appliance. If you already know your Model Number, just enter the first few characters. The photo should be clear and well lit. Please double check your model number and make sure that all letters are capitalized. Please try again or type the Model Number ENr into the field manually. Please contact us if you can't find what you're looking for. We would like to invite you to take part in a short one minute survey. Thank you. If you wish to be contacted by us, please use our regular contact form here, contact Customer Support at 800 9442904, or chat online with a Customer Support representative. Please note that depending on the settings you choose, the full functionality of the website may no longer be available. To find the model number ENr, check the rating plate of your appliance. Use the rating plate finder below to see where it is located on your appliance. Please enter your email address and password below to log in. Instruction manuals contain essential information to operate and maintain your appliance. Buy genuine spare parts direct from Bosch. O reflexo dessa realidade tem sido claramente refletido na demanda de nossos clientes, com impactos diretos nas atividades logisticas, principalmente no que se refere a qualidade e flexibilidade. A qualidade da logistica tem se tornado cada vez mais importante na competitividade de nossos negocios, e um fator crescentemente decisivo no sucesso de nossas estrategias.

A Robert Bosch Ltda entende que os altos niveis de qualidade, tanto de seus produtos quanto de seus servicos, so pode ser obtido em conjunto com Fornecedores que trabalhem com o mesmo foco, ou seja, orientados a seus clientes. Este manual tem como objetivo aprimorar o relacionamento da Robert Bosch Ltda com seus Fornecedores, minimizando o risco de perdas em virtude de naoconformidades. O objetivo final e estabelecer uma relacao cada vez mais clara e transparente com foco na competitividade de nossos negocios. O presente manual foi elaborado para servir como referencia a todas as unidades de negocio e plantas da RBLA Robert Bosch America Latina Ltda e suas afiliadas, assumindo os processos padroes e preferenciais como referencia. Esses processos podem ser suplantados por padroes especificos de cada planta em funcao de especificidades nao tratadas neste manual. Adicionalmente gostaríamos de ressaltar que os padroes e processos abordados neste manual se aplicam as empresas que forneçam para as unidades da RBLA. Fornecedores nacionais com contratos de fornecimento para outras plantas Bosch que nao as localizadas na America do Sul, estao sujeitas as especificidades locais, tratados nos manuais regionais. As precondicoes para isto sao Pronta notificacao de alteracoes de qualquer natureza com impacto em processos com Fornecedores acordos, processos, etc.. Conformidade e monitoramento dos acordos feitos. 1.1 Comunicacao entre o Fornecedor e a BOSCH 1.1.1 Contatos Os Fornecedores devem informar o contato da pessoa responsavel pelo suporte em assuntos relacionados a logistica nome do contato, substituto, endereco eletronico, telefone e fax. A pessoa de contato deve ter experiencia e conhecimento nos diversos assuntos sob sua responsabilidade. 1.1.2 Disponibilidade A principal pessoa de contato designada pelo Fornecedor ou seu substituto deve estar disponivel para contato nos dias uteis das 800h as 1700h. horario local do Fornecedor.

Fora desses horarios e durante periodos de recesso, pessoas qualificadas devem estar acessiveis para lidar com eventuais emergenciais.

### 1.2 Troca de Informacoes Eletronicas

Com o objetivo de agilizar a troca de informacoes comerciais, a Robert Bosch Ltda promove e desenvolve a comunicacao eletronica com seus Fornecedores, com o objetivo de evitar perda de tempo e reduzir custos com a emissao e manuseio de documentos, aumentando assim a confiabilidade, rapidez e transparencia na troca de informacoes. A seguir detalharemos os dois sistemas utilizados pela BOSCH para envio e recebimento eletronico de informacoes EDI convencional, BeSIS Bosch Eletronic Supplier Interchange System, e Portal de Fornecedores. A versao do layout a ser utilizado pelo Fornecedor para o recebimento destas informacoes devera ser solicitada a area de Tecnologia da Informacao da BOSCH. O Fornecedor devera solicitar tambem a area de Tecnologia da Informacao da BOSCH, que providencie o seu cadastro dentro do diretorio de Fornecedores BOSCH Data Center para que a comunicacao eletronica possa ser estabelecida.

#### 1.2.2 Sistema BeSIS Bosch eletronic Supplier Interchange System

O Sistema BeSIS e um sistema de troca de informacoes, baseado na internet, que foi desenvolvido pela BOSCH como uma alternativa ao uso do EDI convencional. Para poder acessar o Sistema BeSIS, o Fornecedor tera que ser previamente cadastrado, onde recebera um codigo de "Usuario" e uma "Senha", e receber as orientacoes necessarias para que possa utilizar ao maximo todos os recursos disponiveis. A responsabilidade em cadastrar o Fornecedor e orientalo quanto a utilizacao do sistema, e do coordenador do sistema BeSIS de cada fabrica BOSCH. No modulo "Aviso de Embarque", o Fornecedor podera consultar o status em transitio ou recebido dos Avisos de Embarques ASN enviados para a BOSCH; realizar o Upload do Aviso de Embarque para a BOSCH; criar um Aviso de Embarque atraves de processo manual.

No modulo "Informacoes Financeiras", o Fornecedor podera consultar o status em aberto ou compensadas das duplicatas a serem pagas a ele pela BOSCH. No modulo "Preferencias" o Fornecedor podera visualizar o perfil do seu usuario cadastrado no Sistema BeSIS, assim como podera alterar a qualquer momento as informacoes relativas a email de contato, telefone comercial, senha e idioma a ser utilizado no sistema. No modulo "Informacoes" o Fornecedor tera acesso a informacoes adicionais sobre o Sistema BeSIS. Faltando 30 dias para expirar a validade da senha do usuario, o Sistema BeSIS comeca a informar a cada acesso, e de forma regressiva, o numero de dias faltantes para expirar a senha. O arquivo eletronico relativo ao Aviso de Embarque, para Notas Fiscais Modelo 1, 1A ou eletronica NFe, deve ser desenvolvido pelo Fornecedor respeitando os respectivos layouts disponibilizados pela BOSCH atraves do Portal de Fornecedores Topico 1.2.4 deste Manual. Os arquivos electronicos de Avisos de Embarques ASN deverao ser enviados para a BOSCH atraves do sistema EDI convencional ou atraves do Sistema BeSIS. Detalhes mais tecnicos e formas de transmissao dos arquivos de Avisos de Embarques serao discutidos na fase de desenvolvimento dos mesmos.

#### 1.2.4 Portal de Fornecedores Bosch

Com o objetivo de tornar mais agil e eficiente a interacao com os Fornecedores BOSCH, foi desenvolvido o Portal de Fornecedores BOSCH, para servir como um canal de comunicacao para a troca de informacoes, envio de comunicados, e integracao de sistemas entre outras facilidades. Atraves deste Portal, o Fornecedor cadastrado acessa um ambiente seguro e restrito aos usuarios da sua empresa, para o compartilhamento de informacoes relacionadas aos departamentos de Compras, Logistica, e Qualidade. Figura 1.3 Para que o Fornecedor possa ter acesso ao Portal de Fornecedores Bosch ele devera possuir um Login e uma Senha cadastrados.

O acesso ao Portal, para os Fornecedores que ainda nao o possuem, deve ser realizado inicialmente mediante solicitacao de cadastro ao seu contato do departamento de Compras, de Logistica ou de Qualidade BOSCH, que avaliara esta solicitacao e posteriormente a encaminhará para o departamento responsavel para a efetivacao do cadastro. Apos liberado e efetivado o cadastro, o sistema de cadastro do Portal de Fornecedores enviara um email com as informacoes necessarias para que o acesso pelo Fornecedor possa ser realizado. Qualquer execucao a esse padrao, por

quaisquer motivos, deve ser objeto de um acordo específico. O Fornecedor checa se os pedidos recebidos estão completos, corretos e plausíveis por exemplo nome do Fornecedor, itens, quantidades e datas estão corretos. Se qualquer discrepância é encontrada, o Fornecedor deve imediatamente alertar o respectivo planejador de materiais da BOSCH. Os pedidos serão considerados como plenamente aceitos datas, quantidade e demais condições de compra caso o Fornecedor não tenha objeção a nenhum dos parâmetros e não avise a BOSCH sobre a não aceitação dentro de dois dias úteis 48 horas a partir do recebimento dos pedidos. A confirmação das ordens somente é requerida em caso de não concordância ao pedido, ou seja, data e quantidade em específico.

1.3.2 Acompanhamento das Ordens O Fornecedor continuamente acompanha as ordens em andamento. O Fornecedor é capaz de fornecer informações sobre o andamento dos pedidos a qualquer momento. Uma metodologia transparente de acompanhamento de pedidos deve ser assegurada. A utilização do Sistema BeSIS neste caso é de fundamental importância. Se qualquer problema venha a ocorrer e tenha algum impacto sobre o cumprimento dos pedidos, o Fornecedor deve imediatamente tomar medidas corretivas. Se não for possível o estabelecimento de acordo, a pessoa responsável do Fornecedor deve envolver seus superiores hierárquicos na busca por uma pronta resolução da divergência.

O dia da semana em que é enviado o plano de remessas BOSCH varia de planta para planta. O plano de remessas contém os próximos pedidos firmes período de dias fixados e definidos por cada planta BOSCH, e para cada material, e uma previsão de consumo a médio prazo, ou seja, para os próximos meses. Tal previsão de consumo não caracteriza a obrigatoriedade da BOSCH em confirmar os pedidos. Sua função é fornecer ao Fornecedor com uma informação sobre demanda prevista com base em nosso planejamento de vendas, possibilitando ao Fornecedor executar, por sua vez, seu próprio planejamento com relação a recursos físicos e humanos.

1.3.4 Gerenciamento da Introdução de Itens Novos ou em Processo de Descontinuidade Durante os períodos de introdução ou descontinuidade da compra de itens, faz-se necessário uma maior flexibilidade por parte do Fornecedor para lidar com contingências características desses períodos. O planejamento de capacidade deve ser coordenado com o Fornecedor caso a caso.

1.4 Controle da Performance Logística A Robert Bosch Ltda. O IFE indica exclusivamente a entrega realizada dos materiais em relação a data do pedido de cada item, acordada previamente com cada Fornecedor. No critério utilizado a nota do IFE pode assumir valores iguais a 0 ou 1.

1.4.1 Forma de Cálculo do IFE O cálculo do IFE é feito de uma forma muito simples e representado pela seguinte equação A Tabela 1.1 exemplifica o critério utilizado para o cálculo da nota do IFE. O exemplo dado na Tabela 1.1 refere-se apenas a entrega de um item e de um mesmo Fornecedor.

<http://www.drupalitalia.org/node/70917>